

Räumdorne für Index-Halter

Werkstoff: HSS 1.3343 – gehärtet

Räumdorne Innensechskant

12 x 40 mm | auch TIN-beschichtet erhältlich

Bestell-nummer	Artikel	D	L	L1	L2	SW 6-kt.	RT
37-1,5	W 37 606.0150	12	40	15	25	1,5	4,5
37-2	W 37 606.0200	12	40	15	25	2	6,0
37-2,5	W 37 606.0250	12	40	15	25	2,5	6,5
37-3	W 37 606.0300	12	40	15	25	3	7,0
37-3,175	W 37 606.03175	12	40	15	25	1/8"	7,0
37-3,5	W 37 606.0350	12	40	15	25	3,5	9,0
37-4	W 37 606.0400	12	40	15	25	4	12,0
37-4,5	W 37 606.0450	12	40	18	22	4,5	12,0
37-5	W 37 606.0500	12	40	18	22	5	12,0
37-5,5	W 37 606.055x0	12	40	18	22	5,5	12,0
37-6	W 37 606.0600	12	40	18	22	6	12,0
37-6,35	W 37 606.0635	12	40	18	22	1/4"	12,0
37-7	W 37 606.0700	12	40	18	22	7	12,5
37-7,938	W 37 606.07938	12	40	18	22	5/16"	12,5
37-8	W 37 606.0800	12	40	18	22	8	13,0
37-9	W 37 606.0900	12	40	18	22	9	14,5
37-9,525	W 37 606.09525	12	40	18	22	3/8"	14,5
37-10	W 37 606.1000	12	40	18	22	10	16,0
37-11	W 37 606.1100	12	40	18	22	11	18,0
37-12	W 37 606.1200	12	40	18	22	12	19,0
37-12,7	W 37 606.1270	12	40	18	22	1/2"	19,0
37-13	W 37 606.1300	12	40	18	22	13	19,0
37-14	W 37 606.1400	12	40	18	22	14	19,0
37-15	W 37 606.1500	12	40	18	22	15	19,0
37-16	W 37 606.1600	12	40	18	22	16	19,0
37-17	W 37 606.1700	12	40	18	22	17	19,0
37-18	W 37 606.1800	12	40	18	22	18	19,0
37-19	W 37 606.1900	12	40	18	22	19	19,0
37-22	W 37 606.2200	12	40	18	22	22	19,0
37-24	W 37 606.2400	12	40	18	22	24	19,0
37-27	W 37 606.2700	12	40	18	22	27	19,0
37-32	W 37 606.3200	12	40	18	22	32	19,0

8 x 30 mm | auch TIN-beschichtet erhältlich

Bestell-nummer	Artikel	D	L	L1	L2	SW 6-kt.	RT
43-1,5	W 43 806.0150	8	30	12	18	1,5	3,6/3,4
43-2	W 43 806.0200	8	30	12	18	2	5,6/5,4
43-2,5	W 43 806.0250	8	30	12	18	2,5	5,8/6,0
43-3	W 43 806.0300	8	30	12	18	3	7,2/7,0
43-3,5	W 43 806.0350	8	30	12	18	3,5	7,5/7,3
43-4	W 43 806.0400	8	30	15	15	4	9,2/9,0
43-4,5	W 43 806.0450	8	30	15	15	4,5	9,2/9,0
43-5	W 43 806.0500	8	30	15	15	5	10,0
43-5,5	W 43 806.0550	8	30	15	15	5,5	10,0
43-6	W 43 806.0600	8	30	15	15	6	11,0
43-6,35	W 43 806.0635	8	30	15	15	6,35	11,0
43-7	W 43 806.0700	8	30	15	15	7	11,0
43-8	W 43 806.0800	8	30	15	15	8	13,0
43-9	W 43 806.0900	8	30	15	15	9	13,0
43-10	W 43 806.1000	8	30	15	15	10	15,0
43-12	W 43 806.1200	8	30	15	15	12	15,0
43-14	W 43 806.1400	8	30	15	15	14	15,0

